

**B4B****BATTERIES4BROADCAST, INC.**

407 South 21 Avenue

Hollywood, Florida 33020  
USA

Phone: 1.888.585.0620

Fax: 954.364.7983

[www.batteries4broadcast.com](http://www.batteries4broadcast.com)[sales@batteries4broadcast.com](mailto:sales@batteries4broadcast.com)**Battery  
Specification  
Model: AM-4080**

Cell:	Panasonic, LG, Sony
Type:	“3-Stud Mount” Li-ion Battery
Voltage:	14.8V
Capacity:	10Ah / 150Wh
Built-in:	Standard Power Tap connector
Suggested operating temp:	-20°C~ +55°C
Dimensions:	101(W) X 152 (L) X 57 (D)mm
Weight:	890g/ 2 lbs
Short circuit:	built-in auto-reset protection circuit
Discharge:	11V
(Different cameras will have different running times based on different shut-off voltage)	
Charging:	16.8V

**Maximum load: 80Watts**Working time with 30W load:

Remain 3 LED:	41 min.
Remain 2 LED:	47 min.
Remain 1 LED:	59 min.

**Total running time: 251 min.**Charged by B4B chargers (full charge):

TC-C01:	332 min.
SM-C02:	177 min.
SM-C04:	271 min.

***CAUTION: When using the auxiliary power connector, please verify the polarity (+/-) is correct when connecting cables and powering accessories. Damage will result if polarity is reversed!***

Aggregate equivalent lithium content: 10.56g

***NOTE: Certain restrictions concerning air-transport apply to lithium batteries, please check with carrier/shipper for more information and guidelines. This battery has aggregate equivalent lithium content which is over and may have travel restrictions on its transport via aircraft.***